




# Liquidtight Flexible Nonmetallic Conduit/Connector

## TYPE - NM2



Contact your local Sales Representative  
[Click Here for Printable Version](#)

				Coil	Footage	Inner	Diameter	Outer	Diameter	List Price
Trade Size	Type	Inside Bend Radius	Wt. (Lbs.)/100 Ft.	Length	Part #	Min.	Max.	Min.	Max.	Price Per 100 FT
1/4"	NM2-140	0.6"	5	100	82000	0.385	0.405	0.560	0.575	\$204.00
3/8"	NM2-10	0.7"	6	100	82001	-	-	-	-	\$228.00
1/2"	NM2-11	0.9"	8	100	82011	-	-	-	-	\$242.00
3/4"	NM2-12	1.1"	10	100	82022	-	-	-	-	\$345.00
1"	NM2-13	1.3"	15	100	82032	-	-	-	-	\$497.00
1-1/4"	NM2-14	1.7"	20	100	82042	-	-	-	-	\$654.00
1-1/2"	NM2-15	1.9"	26	50	82052	-	-	-	-	\$922.00
2"	NM2-16	2.4"	36	50	82062	-	-	-	-	\$1,359.00



See [Chart for Dimensions and Tolerances](#).

### TYPE - NM2

Type NM2 is an Extra Flexible Liquidtight Nonmetallic Tubing. This lightweight tubing cuts easily and installs quickly. It is ideal for wiring protection in tight quarters and for tight bends. The thin flexible PVC skin allows for greater movement for many OEM applications. Used for Wiring Harnesses, Laboratory Equipment, Fiber Optics, Etc.

### CONSTRUCTION:

Co-extruded from both flexible and rigid PVC. The rigid spiral PVC reinforcement is imbedded within the wall of the tubing.

Conforms to CSA 22.2 No. 227.3

UL Recognized File # E174249

**Fittings:**

Intended for use with nonmetallic liquidtight fittings marked FNMC-B. See Type NMLT Connectors for further information.

**Tests Include:**

[WEEE and RoHS Compliant](#)

**STANDARD COLORS:**

Black

**WORKING TEMPERATURES:**

-20°C to 70°C

**Flexibility:** [See the Flexibility Comparison Guide](#)

**Plastic Used: PVC** [See the Chemical Resistance Guide](#)

High Mech. Strength	Listed For Direct Burial	Halogen Free	Low Fire Hazard	Accepts Standard Liquidtight Fittings	Self Extinguish	EMI/RFI Shielding	Oil Resistance	Acid Resistance
					X		X	X