

Type NM

A general purpose, UL and CSA listed, nonmetallic liquidtight conduit offering excellent protection to wiring from abrasion, sunlight, mild acids, alkaline and oils. Often used for air conditioning hook-ups and other outdoor applications.



All Products Proudly Made in the USA

Construction:

- Type NM is a helically wound integral Type B construction. It contains a spiral of rigid PVC reinforcement imbedded within the PVC wall.
- Resistant to Oils and Mild Acids
- Sunlight Resistant (UV)
- Self-Extinguishing
- Dynamic Flexibility, Limited

Application:

Type NM is intended for installation in accordance with Article 356 of the NEC (ANSI/NFPA-70) for Flexible Liquidtight Nonmetallic Conduit (LFNC-B or FNMC-B).

- For containment of 1000 volt and lower potential circuits.
- Listed and marked for outdoor use.
- Listed and marked for direct burial and in poured concrete
- Installations in hazardous (classified) locations:
 - Class I Div. 2 Article 501
 - Class II Div. 1 & 2 Article 502
 - Class III Div. 1 & 2 Article 503
- Electric signs and outdoor lighting over 1000 volts. Article 600.32(A).
- Wiring methods for pools and spas. Article 680.

Conforms to the requirements of Section 14.5.5 of the electrical Standard for Industrial Machinery NFPA-79.

Fittings:

Suitable for use with nonmetallic fittings marked for FNMC-B or LFNC-B for liquidtight flexible nonmetallic conduit Type B or with standard metal liquidtight fittings. See **NMLT connectors** for further information. See **Couplings (Splices)** to reduce waste and conjoin lengths of Type NM conduit.

Continuous lengths on reels available in 1/2" and 3/4" diameters only. Larger sizes available in non-continuous lengths on reels. Sections are tied or taped and must be separated for use.

Product Information

CERTIFICATIONS & COMPLIANCE



Listed File # E79308
Conforms to Underwriters
Laboratories Standard ANSI/UL
1660 Type B.



Certified File #LL230485
Conforms to CSA 22.2 No. 227.2
Type B.



WEEE and RoHS Compliant

ARRA: For ARRA Certification
Letter, please [click here](#)



BABA Compliant

STANDARD COLORS

Machine Tool Gray. Also available in black. **Other colors available upon request.**

WORKING TEMPERATURES:


-20°C to 80°C Dry / 60°C Wet / 70°C Oil

-4°F to 176°F / 140°F Wet / 158°F Oil


Markets:

Cell Towers, Construction, DataComm, Renewable Energy, Ship Building,
Telecommunications, Utilities, Wastewater Treatment

For higher temperature version, see **Type NMHT**.



NM Type B



Product Table

US Trade Size	ISO (MM)	CSA (MM)	Type	Internal Diameter		Outside Diameter		Inside Bend Radius	Weight (Kgs) per 30 meters	Standard Length			
				Min (MM)	Max (MM)	Min (MM)	Max (MM)	Static (MM)		Carton (Mtrs)	Part #	Reel (Mtrs)	Part #
3/8"	16	12	NM-10	12.3	12.8	17.5	18.0	51	5	30	81001	300	81004
1/2"	20	16	NM-11	15.8	16.3	20.8	21.3	83	5	30	81011	300	81014
3/4"	25	21	NM-12	20.8	21.3	26.2	26.7	108	7	30	81022	150	81024
1"	32	27	NM-13	26.4	27.1	32.8	33.4	165	11	30	81032	120	81034
1 1/4"	40	35	NM-14	35.1	35.8	41.4	42.2	203	15	30	81042		
1 1/2"	50	41	NM-15	40.0	40.6	47.4	48.3	229	19	15	81052		
2"	63	53	NM-16	51.3	51.9	59.4	60.3	279	27	15	81062		

related products



Type NMHT

This version of Type NM is designed to withstand high temperature environments. NMHT can be used to contain conductors having insulation materials with higher temperature ratings.



Type NM2

Type NM2 is an extra-flexible liquidtight nonmetallic tubing. This lightweight tubing cuts easily and installs quickly. It is ideal for wiring protection in tight quarters and for tight bends. The thin, flexible

[see product detail »](#)



Type LNMP

This UL and CSA listed nonmetallic liquidtight conduit is ideally suited for continuous flexing situations. It is often specified in "Power Track" or cable carrier installations and on industrial robots. It does not contain a metal core which could fatigue from repeated flexing or vibration.

[see product detail »](#)

PVC skin allows for greater movement than Listed nonmetallic conduits.

[see product detail »](#)



Type NMLT & NMSC

Type NMLT and NMSC nonmetallic connectors are intended to be used with liquidtight nonmetallic conduit Type B. (NM, NMHT, NMFG and NM2.) They are not to be used with Type A (LNM-P) conduit or steel conduit.

[see product detail »](#)